

## Tech Data

## CABLE AND FIBRE OPTIC POWER SPEAKER

### Description



Speaker cable. Flexible bare copper conductor insulated in polyvinyl chloride with twisted cores and covered by polyvinyl chloride. Cable with 2, 4 or 8 conductors.

### Applications

Cable for speaker.

## Tech Data

## CABLE AND FIBRE OPTIC POWER SPEAKER

### Physical Characteristics

SPEAKER CABLE	Conductor		Insulation	
	Material: Bare stranded Cu (Copper)		Material: PVC	
	Composition Flexible, V Class (UNE-EN 60228/HD 383 52)		Colour: DIN 47100	
	Outer Sheath			
Material: PVC (Polyvinyl Chloride)				
Colour: <b>BLACK</b>				
REF.	Cond. x Section	Conductor	∅ Insulation	∅ Sheath
M10844	2 x 2.5 mm <sup>2</sup>	48 x 0.245 mm	3.2 ± 0.15 mm	8.4 ± 0.2 mm
M10845	2 x 4 mm <sup>2</sup>	82 x 0.245 mm	4.1 ± 0.15 mm	11.0 ± 0.2 mm
M11324	4 x 2.5 mm <sup>2</sup>	48 x 0.245 mm	3.4 ± 0.15 mm	11.0 ± 0.2 mm

## Tech Data

## CABLE AND FIBRE OPTIC POWER SPEAKER

### Electrical Characteristics

Voltage Rating	300 V
Voltage Test	2.5 KV
Temperature Rating	Up to max +60°C
Resistance at 20°C	According to the standard IEC 228/HD 38352
Resistance to flame propagation	According to the standard IEC 332-1

### Environment

RoHS (*Restriction of Hazardous Substances*) Directive 2011/65/EU

### Applicable Regulations

BT 93/68 CEE

2014/35/EU

2006/1907/CE



Web: [www.pinanson.com](http://www.pinanson.com)  
@: [pinanson@pinanson.com](mailto:pinanson@pinanson.com)

PINANSON S.L  
Avda. Constitucion, 40. Mondejar (Guadalajara). SPAIN.  
Telephone: +34 949 385 444 · Fax: +34 949 385 643

Review: April 2019

For possible changes due to continuous product improvements; Pinanson S.L. reserves the right to change the showed data in this document without notice. The data presented here correspond to the time it was compiled.