


Tech Data

CONTROLLERS AMPLIFIER HEADPHONE 2CH



2 output amplifier drawing

Description

Headphone signal amplifier with up to 4 headphone outputs with level control each output.

!! Excessive volume can damage your ears or headphones. Before you start using the device, please, turn down the volume to the minimum level 0 (the knob toward the left). Make sure you use an appropriate volume for listening.

Tech Data

CONTROLLERS AMPLIFIER HEADPHONE 2CH

Tech Specification

Line Input

Connector	Impedance	Max. Input level
Jack TS 1/4", STEREO	100 K Ω	+ 15 dBu

Headphone Outputs

Connector	Impedance	Max. Output level
Jack TS 1/4", STEREO	80 Ω	Aprox. 40 mW en 100 Ω

Power

12 V Direct Current/ 150 mA

Physical Characteristics: depend on the format

Choose format	MF portable format (see dimensions)
	Rack mount format (see dimensions)

Tech Data

CONTROLLERS AMPLIFIER HEADPHONE 2CH

Measurements



Audio measurements are done with *Audio Precision APx515 analyser*.



Web: www.pinanson.com
@: pinanson@pinanson.com

PINANSON S.L
Avda. Constitucion, 40. Mondejar (Guadalajara). SPAIN.
Telephone: +34 949 385 444 · Fax: +34 949 385 643

Review: March 2015

For possible changes due to continuous product improvements; Pinanson S.L. reserves the right to change the showed data in this document without notice. The data presented here correspond to the time it was compiled.