


## Tech Data

## PATCH PANEL OPTICAL FIBER LC-LC



### Description

- Optical Fiber panel with **LC-LC duplex** or **simple** connector. Without tray.
- These connectors have an **A-B codification** to ensure the correct polarity for bidirectional communications.

### Applications

Installations with optical fiber connections systems.

## Tech Data

## PATCH PANEL OPTICAL FIBER LC-LC



### Technical Characteristics

PANEL	LC-LC CONNECTORS		
<b>Patchbay</b> Extruded aluminium Alloy 6063 <b>Colour</b> Black RAL 9005 <b>Tie cable bar</b> 8 mm steel F1 calibrated <b>Label profile</b> Extruded aluminium (No tray)	MULTIMODE <b>PC</b> polishing	SINGLEMODE <b>UPC</b> polishing	SINGLEMODE <b>APC</b> polishing
	LC-LC multimode connector with a pressure metal ring (phosphor bronze).	LC-LC single mode with pressure ring ceramic (zirconia).	
	<b>Typical Attenuation</b> 0.20 dB <b>Max. Attenuation</b> 0.40 dB <b>Attenuation</b> (500 cycles) 0.1 dB <b>Work Temperature</b> -40 a 85 °C <b>Retention force</b> 300 N <b>Colour</b> Beige	<b>Typical Attenuation</b> 0.15 dB <b>Max. Attenuation</b> 0.30 B <b>Attenuation</b> (500 cycles) 0.1 dB <b>Work Temperature</b> -40 a 85 °C <b>Retention force</b> 300 N <b>Colour</b> Blue	<b>Typical Attenuation</b> 0.1 dB <b>Max. Attenuation</b> 0.20 dB <b>Attenuation</b> (500 cycles) 0.1 dB <b>Work Temperature</b> -40 a 85 °C <b>Retention force</b> 300 N <b>Colour</b> Green For high Reflection loss >60 dB

## Tech Data

## PATCH PANEL OPTICAL FIBER LC-LC

### Physical Characteristics



### Regulations

EN 187000	GENERIC SPECIFICATION: OPTICAL FIBRE CABLES
CEI 60794	
UNE-EN 50265 (IEC 60332-1)	FIRE TESTS
UNE-EN 50268 (IEC 61034-1/2)	
ESTÁNDAR EIA-310-D	STANDARD RACK ESPECIFICATION
IEC 60297-2/60297/3	MECHANICAL STRUCTURES FOR ELECTRICAL EQUIPMENT
CONFORMIDAD CE	CE MARKING
NORMA RoHS	DANGEROUS SUBSTANCES RESTRICTION

## Tech Data

## PATCH PANEL OPTICAL FIBER LC-LC



Web: [www.pinanson.com](http://www.pinanson.com)  
@: [pinanson@pinanson.com](mailto:pinanson@pinanson.com)

PINANSON S.L  
Avda. Constitucion, 40. Mondejar (Guadalajara). SPAIN.  
Telephone: +34 949 385 444 · Fax: +34 949 385 643

**Review: March 2015**

For possible changes due to continuous product improvements; Pinanson S.L. reserves the right to change the showed data in this document without notice. The data presented here correspond to the time it was compiled.